RESIDUAL RISK ASSESMENT



WHEREVER POSSIBLE, RISK IS DESIGNED-OUT OF THIS PROJECT DURING THE DESIGN
PROCESS. WHERE THIS IS NOT POSSIBLE, THE RISK WILL BE MINIMISED AND ANY RESIDUAL RISK WILL BE NOTED AND INDICATED BY THE

. SPECIAL CARE IS TO BE TAKEN WHEN WORK AT HEIGHTS IS IN PROGRESS. APPROPRIATE EDGE PROTECTION IS TO BE PROVIDED. MATERIALS, FORMWORK MEMBERS OR ANY OBJECTS ARE NOT TO SE STACKED AGAINST THE EDGE PROTECTION. SITE TEAM ARE TO CONSIDER THE RISK OF FALLS FROM HEIGHT WHILST INSTALLING, DISMANTLING AND MAINTAINING THE SUPPORT SYSTEM AND EDGE

. ALL LIFTING OPERATIONS ARE TO BE CONDUCTED BY COMPETEN ERSONNEL ONLY. ALL LIFTING EQUIPMENT IS TO BE INSPECTED EFORE COMMENCING WORKS AND CLASSIFIED AS SAFE TO USE PECIAL CARE IS TO BE TAKEN WHEN LIFTING OPERATIONS ARE ERFORMED AND EQUIPMENT IS TO BE TRANSPORTED OVER THE ORKING AREAS. ALL GROUND PERSONNEL IS TO BE MADE AWARE HAT LIFTING OPERATIONS ARE TAKING PLACE.

 REGULAR INSPECTIONS ARE REQUIRED TO ENSURE INTEGRITY OF THE SYSTEM IS MAINTAINED. ANY DAMAGED PARTS SHOULD BE REPLACED AT THE EARLIEST OPPORTUNITY. IF HAZARD IS NOTICED MUST BE REPORTED TO THE SUPERVISOR IMMEDIATELY.

FOLLOW POUR RATES INDICATED ON THE DRAWING WITH ATTENTION TO THE MAX. DESIGN PRESSURE AND THE RATE OF RIS

. MAKE SURE CONCRETE STRENGTH IS SUFFICIENT TO SUPPORT ITS



IMPORTANT:

MAX. CONCRETE PRESSURE

45 kN/m

1.9M FAST FORM WALL SYSTEM SIDE VIEW WITH CORNER SHOWN

A-A: 1:25





ALL DIMENSIONS IN MILLIMETRES UNLESS NOTED OTHERWISE.

PLYWOOD VERTICAL JOINTS TO FALL AT THE CENTRE OF UPRIGHTS.

PLYWOOD HORIZONTAL JOINTS TO FALL AT THE CENTRE OF HORIZONTAL JOINING MEMBERS. IF THE JOINT FALLS IN BETWEEN OF BRACES, ADD AN ADDITIONAL MEMBER.

3 TIE BARS THROUGH EACH UPRIGHT AS STANDARD.


CORNER BRACE ACCESSORIES TO BE FIXED INDEPENDENTLY USING WALER TIE ACCESSORIES.

TIE BARS CAN BE POSITIONED THROUGH HORIZONTAL JOINING MEMBERS IF OPPOSITE UPRIGHT'S HOLES DO NOT ALIGN.

MINIMUM CLASS 8.8, MI6 TENSILE BOLTS TO BE USED FOR FIXING THE WALL SYSTEM MEMBERS TOGETHER.

FOR DETAILS ON CORNER SET-UP, PLEASE REFER TO DRAWING NO FFS-WSTC.

ALL TIMBER MEMBERS SHOWN TO BE PROVIDED BY CLIENT.



IMPORTANT:

FORCES FROM HEAPING, SURGE AND IMPACT.

PROP FIXING

DETAIL:

1:5


- MI6 GRADE 8.8 LONG TENSILE BOLT


COSTUMER IS TO ENSURE THAT DURING POUR OPERATIONS CONCRETE IS PLACED IN AN EVEN MANNER PREVENTING THE IMBALANCE OF ANY FORCES. CONCRETE PLACEMENT IS TO BE CONTROLLED TO AVOID ADVERSE

STOP-END INTERNAL CORNER ACCESSORY

PROP FIXING DETAIL

CORRECT POSITION OF CONCRETE BOLTS: 1:5





IMPORTANT:

CONSULT YOUR TEMPORARY WORKS DEPARTMENT BEFORE USING THIS DESIGN FOR CONSTRUCTION.



IMPORTANT:

ALL CONCRETE HOLDING DOWN BOLTS TO BE INSTALLED ACCORDING TO THE MANUFACTURER TECHNICAL APPROVAL AND INSTALLATION GUIDES AND INTO STRUCTURALLY SOUND CONCRETE TO ENSURE A SECURE FIXING

REVISION	DATE	DESCRIPTION	SIGNED
0	4/06/15	ORIGINAL VERSION	K.P.
А	4/06/16	ANNUAL REVISION	K.P.



Fast-Form www.fastformsystems.com info@fastformsystems.com

Tel South: 00 44 (0) 0203 507 1832 / 507 1833 / 507 1834

Tel North: 00 44 (0) 1472 488230 / 488660 / 485640



Head Office: Unit 1 Estate Road 6 Grimsby N.E.Lincs **DN31 2TG**

LEGAL NOTICE:

Fast Form ™ is the Trade Mark of Fast-Form Systems Ltd and all designs are copyright and intellectual property of Fast-Form Systems Omega Business Park Ltd and may not be reproduced or used without permission. Fast Form ™ is covered by the following Patents: granted GB2508263 / GB2533172 Patents Pending GB 1616005.3 / GB 1506126.0 / US-2016-0194887 / PCT W02016 / 110663 / EP 14780541.0 / PCT GB2014 / 052586. Copyright or Trade Mark infringements will be prosecuted, If you see any similar bracket in operation without our name on it please send us an email to info@fastformsystems.com we offer a reward for all successful prosecutions.

Drawn By: Karol Podsiadlo

Date: 04/06/15 Rev: A

Designed by: Karol Podsiadlo Drawing no: FFS-19WS2

Project: 1.9m Fast Form Wall System

Drawing title: Side View With Corner Shown